



MOTOR WITH PTC THERMAL PROTECTION blue-blue 130°C

Power [kW]	Duty Cycle	Base speed [rpm]	Base freq. [Hz]	Base voltage Δ [V]	Base voltage Y [V]	Protection	Ins. Cl.
2.2	S1	18000	300	220	380	IP54	F
Min speed [rpm]	Max speed [rpm]	Max freq. [Hz]	Absorb. Δ [A]	Absorb. Y [A]	Part number on nameplate		
6000	24000	400	8.6	5.0	COM41470533		
Balancing according to ISO 1940 - G2.5 @ 24000 rpm	Balancing type	pool type full key	pool type half key	Peso / weight	8.45 kg		
Tolleranze non quotate / unlisted tolerances: ±0.5mm		vvv = 0.8 ✓	vv = 3.2 ✓	▽ = 12.5 ✓	~ = 9 ✓		
Smussi non quotate / unlisted chamfers: ±0.5mm							
rev. n°	description					date	signature
00	Emissione					25/02/2016	D. Bottarel
drawn - date	approved - date	checked - date	sostituisce il			foglio / sheet	scala
D. Bottarel - 25/02/2016	S. Perli - 25/02/2016	S. Perli - 25/02/2016	sostituito dal			1 / 1	1:2
Il presente disegno è di proprietà esclusiva di Teknomotor S.r.l. La riproduzione totale e/o parziale e la divulgazione a terzi, senza nostro esplicito consenso scritto, verrà perseguita secondo i termini di legge in vigore.							

TEKNOMOTOR

Teknomotor S.r.l.
Via Argenega 31, I-32038 Quero Vas (BL)
www.teknomotor.com

Title
4147-C-DB-P-ER25-SV-HY-RH

Customer
Catalogo

Drawing code
COM41470533

