




Power [kW]	Duty Cycle	Base speed [rpm]	Base freq. [Hz]	Base voltage Δ [V]	Base voltage Y [V]	Protection	Ins. Cl.		
3.3	S1	18000	300	220	380	IP54	F		
Min speed [rpm]		Max speed [rpm]	Max freq. [Hz]	Absorb. Δ [A]	Absorb. Y [A]	Part number on nameplate			
6000		18000	300	13.7	7.9	51600190			
Balancing: G2.5 - ISO 1940 @ maximum motor speed		Balancing type		tool type full key	tool type half key	Peso / weight			
						10.35 kg			
Tolleranze non quotate / unlisted tollerances: ±0.5mm Smussi non quotati / unlisted chamfers: ±0.5mm				$\nabla = 0.8 \nabla$	$\nabla = 3.2 \nabla$	$\nabla = 12.5 \nabla$	$\sim = \nabla$	Title	
								5160-A-SB-P-ER25	
rev. n°	description			date	signature	Customer			
00	Emissione			21/07/2015	Ing. Bottarel	Catalogo			
						Drawing code		Drawing n°	
						COM51600190		1627	
drawn - date	approved - date	checked - date	sostituisce il			foglio / sheet	scala	A4	
Ing. Bottarel - 21/07/2015	Ing. Perli - 21/07/2015	Ing. Perli - 21/07/2015	sostituito dal			1 / 2	n.d.	