




Power [kW] 2.2	Duty Cycle S1	Base speed [rpm] 18000	Base freq. [Hz] 300	Base voltage Δ [V] 220	Base voltage Y [V] 380	Protection IP54	Ins. Cl. F	
Min speed [rpm] 6000	Max speed [rpm] 24000	Max freq. [Hz] 400	Absorb. Δ [A] 9.0	Absorb. Y [A] 5.2	Part number on nameplate COM41470563			
Balancing: G2.5 - ISO 1940 @ maximum motor speed		Balancing type		tool type full key 	tool type half key 	Peso / weight 7.94 kg		
Tolleranze non quotate / unlisted tollerances: ±0.5mm Smussi non quotati / unlisted chamfers: ±0.5mm				$\nabla = 0.8 \nabla$	$\nabla = 3.2 \nabla$	$\nabla = 12.5 \nabla$	$\sim = \nabla$	Title 4147-C-DB-HSK32C-HY
rev. n° 01	description Aggiunti fori M6 sui lati larghi				date 11/01/2017	signature E. Gaspari	Customer Catalogo	
rev. n° 00	description Emissione				date 14/10/2016	signature D. Bottarel	Drawing code COM41470563	Drawing n° 4659
drawn - date E. Gaspari - 11/01/2017	approved - date S. Perli - 11/01/2017	checked - date S. Perli - 11/01/2017	sostituisce il sostituito dal		foglio / sheet 1 / 1	scala 1:2	