



Motor PTC thermal protector

Power [kW]	Duty Cycle	Base speed [rpm]	Base freq. [Hz]	Base voltage Δ [V]	Base voltage Y [V]	Protection	Ins. Cl.	<b>TEKNOMOTOR</b>
2.2	S1	18000	300	220	380	IP50	F	
Min speed [rpm]		Max speed [rpm]	Max freq. [Hz]	Absorb. Δ [A]	Absorb. Y [A]	Part number on nameplate		
6000		24000	400	8.6	5.0	Title		
Balancing according to ISO 1940 - G2.5 @ 24000 rpm		Balancing type		tool type full key	tool type half key	Peso / weight		
						8.66 kg		
Tolleranze non quotate: UNI EN 22768 fH Smussi non quotati: 0.5mm				$\nabla = 0.8 \sqrt{\quad}$	$\nabla = 3.2 \sqrt{\quad}$	$\nabla = 12.5 \sqrt{\quad}$	$\sim = \nabla$	Title
						4147-C-DB-P-ER25-HY-RH-SV		
rev. n°	description			date	signature	Customer		
00	Emissione			14/12/2020	D. Bottarel	Catalogo		
						Drawing code		
						COM41470635		
drawn - date	approved - date	checked - date	sostituisce il		foglio / sheet	scala	A4	
D. Bottarel - 14/12/2020	S. Perli - 14/12/2020	S. Perli - 14/12/2020	sostituito dal		1 / 1	n.d.		