



**PLUG CONNECTION**  
 pin #1: PTC  
 pin #2: PTC  
 pin #3: U  
 pin #4: V  
 pin #5: W

Coolant type: Water + 10% Ethylene Glycol + corrosion inhibitors  
 Temperature setting: +25±3°C (+77±5°F)  
 Minimum flow rate: 3 litres/minute  
 Maximum 3bar

Power [kW]	Duty Cycle	Base speed [rpm]	Base freq. [Hz]	Base voltage Δ [V]	Absorb. Δ [A]	Base voltage Y [V]	Absorb. Y [A]
2.2	S1	24000	400	220	8.4		
Power [kW]	Duty Cycle	Base speed [rpm]	Base freq. [Hz]	Base voltage Δ [V]	Absorb. Δ [A]	Base voltage Y [V]	Absorb. Y [A]
Min speed [rpm]		Max speed [rpm]	Max freq. [Hz]	Protection	Ins. Cl.	Part number on nameplate	
6000		36000	600	IP54	F	COMTC410018	
Balancing according to ISO 1940 - G2.5 @ 36000 rpm		Balancing type		tool type full key	tool type half key	Peso / weight 6,99 kg	
rev. n°	description			date	signature	Customer	Drawing code
00	Emissione			11/01/2024	D. Bottarel	Catalogo	COMTC410018
drawn - date		approved - date	checked - date	sostituisce il		foglio / sheet	scala
D. Bottarel - 11/01/2024		S. Perli - 11/01/2024	S. Perli - 11/01/2024	sostituito dal		1 / 1	n.d.



Teknomotor S.r.l.  
 Via Argenegea 31, I-32038 Quero Vas (BL)  
 www.teknomotor.com

Title  
**ATC41-C-2DB-ISO20-SN-HY-LC**

Tolleranze non quotate: UNI EN 22768 fH  
 Smussi non quotati: 0.5 mm  
 Rugosità secondo UNI ISO 1302

