c c <u>Effective (Outer) Diameter</u> <u>37.00m</u> <u>Pitch Diameter</u> <u>38.20mm</u> <u>Weight</u> <u>0.11kg</u> <u>1temref</u> <u>Quantity</u> <u>Title/Name, designation, material, dimension etc</u> <u>Article No./Reference</u> <u>Drawn by</u> <u>Checked by</u> <u>Approved by - date</u> <u>File name</u> <u>Date</u> <u>Scale</u>		1	2		3		4			5		6	_
ATS Puley with 24 Tech Designed for use with 25mm wide belts c c c c c c c c c c c c c c c c c c c	Γ			RevNo	Revision note	e				Date	Signatur	e Checked	ł
Effective (Outer) Diameter 37.00mm Pitch Diameter 38.20mm Weight 0.11kg With Flanges? yes Material Aluminium Units mm Tolerances ±/0.1mm	A B C	Designed for use w	Teeth ith			28	7 7 0026				42		в
Material Aluminium Units mm Tolerances ±/0.1mm	D	Pitch Diameter Weight	38.20mm 0.11kg	Drawn by		Title/Name, d	-			Article No Date	as a bore o ./Reference	f 8mm e Scale	
Units mm 6415 AT5 Pulley 36-AT5 Z=24 Edition Sheet													-
Tolerances+/-0.1mmO4IJ6415 AT5 Pulley 36-AT5 Z=24 for 25mm wide beltsEditionSheet 1 OF 1					<u>/ / C</u>	_						ו	
				04	+ 10			6415 AT5 Pulley for 25mm wide	415 AT5 Pulley 36-AT5 Z=24 or 25mm wide belts 5		Edition		