




Power [kW] 1.8	Duty Cycle S1	Base speed [rpm] 12000	Base freq. [Hz] 200	Base voltage Δ [V] 220	Base voltage Y [V] 380	Protection IP54	Ins. Cl. F	
Min speed [rpm] 6000		Max speed [rpm] 12000	Max freq. [Hz] 200	Absorb. Δ [A] 8.0	Absorb. Y [A] 4.6	Part number on nameplate COM41470513		
Balancing according to ISO 1940 - G2.5 @ 12000 rpm		Balancing type		tool type full key 	tool type half key 	Peso / weight 7.24 kg		Teknomotor S.r.l. Via Argenege 31, I-32038 Quero Vas (BL) www.teknomotor.com
Tolleranze non quotate: UNI EN 22768 fH Smussi non quotati: 0.5mm				$\nabla = 0.8 \nabla$	$\nabla = 3.2 \nabla$	$\nabla = 12.5 \nabla$	$\sim = \nabla$	
rev. n° 00	description Emissione				date 10/11/2015	signature D. Bottarel	Customer Catalogo	
drawing - date D. Bottarel - 10/11/2015		approved - date S. Perli - 10/11/2015	checked - date S. Perli - 10/11/2015	sostituisce il sostituito dal		Drawing code COM41470513		foglio / sheet 1 / 1
D. Bottarel - 10/11/2015		S. Perli - 10/11/2015	S. Perli - 10/11/2015	sostituisce il sostituito dal		scala 1:2		